

Carbon Dioxide Gas Cylinder - Aluminum

Specifications

Sales Part Number	Service Pressure		Capacity CO ₂ 68% Fill		Capacity N ₂		Outside Diameter		Overall Length		Empty Weight		Minimum Internal Volume		Minimum Water Weight		Thread Size UNF
	psi	bar	lbs	kg	cu ft	liters	in	mm	in	mm	lbs	kg	cu in	liters	lbs	kg	
C1.2	1800	124	1.3	0.6	3.6	102.1	3.21	81.41	9.5	241.1	1.5	0.7	51	0.8	1.84	0.83	0.750-16UNF-2B, 0.625-18UNF-2B
C1.5	1800	124	1.6	0.7	4.6	130.2	3.21	81.41	11.5	292.1	1.8	0.8	65	1.1	2.34	1.06	0.750-16UNF-2B
C218	1800	124	2.0	0.9	5.8	164.2	4.38	111.13	9.0	228.6	3.0	1.4	82	1.3	2.96	1.34	0.750-16UNF-2B
C25H	1800	124	2.5	1.1	7.2	204.3	4.38	111.13	10.4	263.5	3.4	1.5	102	1.7	3.68	1.67	0.750-16UNF-2B
C005	1800	124	5.0	2.3	14.5	410.5	5.25	133.35	14.2	361.6	7.6	2.8	205	3.4	7.39	3.35	1.125-12UNF-2B, 0.750-14NGT
C010	1800	124	10.0	4.5	28.9	817.1	6.89	175.01	16.6	422.3	12.9	5.9	408	6.7	14.71	6.67	1.125-12UNF-2B
C015	1800	124	15.0	6.8	43.3	1225.6	6.89	175.01	23.2	589.0	17.2	7.8	612	10.0	22.07	10.01	1.125-12UNF-2B
C020	1800	124	20.0	9.1	57.7	1634.1	8.00	203.20	23.3	591.6	25.1	11.4	816	13.4	29.42	13.35	1.125-12UNF-2B, 0.750-14NGT
C035	1800	124	35.0	15.9	101.1	2861.7	8.00	203.20	38.0	966.3	37.2	16.9	1429	23.4	51.53	23.37	1.125-12UNF-2B
C050	1800	124	50.0	22.7	144.3	4085.3	8.60	218.44	46.3	1176.7	50.6	22.9	2040	33.4	73.56	33.37	1.125-12UNF-2B

UTTAM AIR PRODUCTS PVT. LTD.
 F-90/5, Okhla Industrial Area, Phase-1
 New Delhi- 110 020, INDIA

Tel : 91 (11) 26817357, 26817410, 26810820, 26817630, 51611842, 51611843

Fax : 91 (11) 26816201

Email : karan.bhatia@uttam.com

© 2005 UTTAM

