

Fire Extinguisher Cylinders - Aluminium

Specifications - 6061 Aluminium

| C02 Capacity | Diameter | Length | Weight | Filling Ratio | Water Capacity | Test Pressure | Thread | Specification |
|--------------|----------|--------|--------|---------------|----------------|---------------|-----------|---------------|
| kg | mm | mm | kg | | litres | bar | | |
| 2 | 102 | 495 | 2.95 | 0.75 | 2.67 | 310 | 25E/M25 | 97/23/EC |
| 2 | 102 | 545 | 2.88 | 0.675 | 3 | 250 | 25E | 97/23/EC |
| 2 | 111 | 475 | 2.15 | 0.667 | 3 | 250 | M25 | 97/23/EC |
| 2 | 111 | 435 | 3.15 | 0.75 | 2.67 | 310 | 25E | 97/23/EC |
| 2 | 111 | 455 | 2.65 | 0.667 | 3 | 243 | 25E | 97/23/EC |
| 2 | 111 | 445 | 2.35 | 0.667 | 3 | 212 | M25 | 97/23/EC |
| 2 | 117 | 415 | 2.7 | 0.667 | 3 | 243 | 25E/M25 | 97/23/EC |
| 2 | 117 | 410 | 2.4 | 0.667 | 3 | 212 | M25 | 97/23/EC |
| 2 | 117 | 410 | 3.1 | 0.75 | 2.67 | 310 | 25E/M25 | 97/23/EC |
| 2 | 117 | 394 | 3.1 | 0.75 | 2.7 | 250 | 25E & M25 | 97/23/EC |
| 2 | 117 | 432 | 3.35 | 0.667 | 3 | 250 | 25E & M25 | 97/23/EC |
| 5 | 152 | 580 | 5.55 | 0.667 | 7.5 | 212 | M25 | 97/23/EC |
| 5 | 152 | 570 | 7.5 | 0.75 | 6.67 | 310 | 25E/M25 | 97/23/EC |
| 5 | 152 | 595 | 6.35 | 0.667 | 7.5 | 243 | 25E/M25 | 97/23/EC |
| 5 | 152 | 625 | 7.86 | 0.675 | 7.86 | 250 | M25 | 97/23/EC |
| 5 | 152 | 620 | 7.65 | 0.667 | 7.65 | 250 | 25E | 97/23/EC |
| 5 | 152 | 565 | 7.3 | 0.75 | 6.7 | 250 | 25E & M25 | 97/23/EC |
| 5 | 152 | 623 | 7.8 | 0.667 | 7.5 | 250 | 25E & M25 | 97/23/EC |

Specifications - 2001 Aluminium

| | | | | | | | | |
|---|-------|-----|-----|-------|-----|-----|-----|----------|
| 2 | 102.8 | 502 | 2.6 | 0.667 | 3 | 250 | 25E | 97/23/EC |
| 5 | 146 | 630 | 5.8 | 0.667 | 7.4 | 250 | 25E | 97/23/EC |

UTTAM AIR PRODUCTS PVT. LTD.
F-90/5, Okhla Insutrial Area, Phase-1
New Delhi- 110 020, INDIA

Tel : 91 (11) 26817357,26817410,26810820,26817630,51611842,51611843

Fax : 91 (11) 26816201

Email : karan.bhatia@uttam.com

© 2005 UTTAM

