

Life Support Gas Cylinders - DOT Hoop Wrap Fiberglass

Specifications

Sales Part Number	Service Pressure		Air Capacity		Outside Diameter		Overall Length		Empty Weight		Min. Internal Volume		Min. Water Weight		Thread Size UNF
	psi	bar	cu ft	liters	in	mm	in	mm	lbs	kg	cu in	liters	lbs	kg	
L08W	3000	207	8.3	235.9	3.26	82.78	13.4	341.3	2.7	1.2	73	1.2	2.63	1.19	0.750-16 UNF-2B
L15W	3000	207	15.3	433.3	4.44	112.78	13.1	333.4	4.6	2.1	134	2.2	4.83	2.19	0.750-16 UNF-2B, 0.875-14 UNF-2B, 0.750-14 NPSM
L17A	4500	310	17.5	495.3	3.84	97.54	15.3	388.4	4.4	2.0	111	1.8	3.99	1.81	0.750-16 UNF-2B, 0.875-14 UNF-2B
L23W	4500	310	22.8	645.1	3.84	97.54	19.4	492.5	5.9	2.7	144	2.4	5.19	2.36	0.875-14 UNF-2B
L24W	3000	207	24.0	679.7	5.31	134.87	14.1	358.9	6.4	2.9	210	3.4	7.57	3.43	0.750-16 UNF-2B
L45W	4500	310	45.0	1274.4	5.39	137.01	19.8	501.7	11.5	5.2	285	4.7	10.28	4.66	0.875-14 UNF-2B, 1.125-12 UNF-2B
L45N	2216	153	45.0	1274.4	6.74	171.20	20.0	506.8	11.8	5.4	523	8.6	18.86	8.55	0.750-16 UNF-2B, 0.750-14 NPSM

3 year retest required on all DOT hoop wrap fiberglass Luxfer cylinders.

UTTAM AIR PRODUCTS PVT. LTD.
F-90/5, Okhla Insutrial Area, Phase-1
New Delhi- 110 020, INDIA

Tel : 91 (11) 26817357, 26817410, 26810820, 26817630, 51611842, 51611843

Fax : 91 (11) 26816201

Email : karan.bhatia@uttam.com

© 2005 UTTAM

